

CORRIGENDUM-1 IN TENDER NO. GEM/2026/B/7819972

DATED 01-08-2026 (PRE-BID QUERY, PRE-BID HELD ON 07/08/2026 AT GIL CONFERENCE ROOM)

Sr.No.	Requirement as per tender terms (Specification Sheet)	Request for amendment in tender terms	Tenderer Response
	2/ 4MP Bullet Camera:-		
1	Type 1/2.7" Progressive Scan CMOS Sensor or better	Kindly change this with 1/2.8	Type 1/2.7" 1/2.8 Progressive Scan CMOS Sensor or better
2	IR Illumination Range (mtr):- 60 or better	kindly change this with 50 m	60 50 m or better
3	Video Compression:- H.265+, H.265, H.264+, H.264	Kindly change this with H.265, H.264,MJPEG	H.265+, H.265/ H.264+/ H.264/MJPEG
4	Certification:- NABL-approved Lab/STQC Lab with equivalent IEC standard (IEC 62368-1) before the date of publishing of the RFP.	Kindly remove this	We kindly request the department to remove this certification requirement for the Network Video Recorder (NVR) or accept the applicable BIS safety compliance as per the relevant Indian standards. IEC 62368-1 certification through an NABL approved/STQC laboratory use for IP Camera only. For NVR BIS Required

12:00 PM)

**Executive Engineer
Capital Project Elect. Dn.
Gandhinagar**

2MP PTZ Camera 30X:-

1.	Video Compression:- H.265, H.264 (The camera OEM Should be a genuine manufacturer and should be an official valid H.265 HEVC licensee and should be listed on HEVC website at the time of submitting bid.)	Kindly change this with H.265, H.264, MJPEG	H.265/H.264 (The camera OEM Should be a genuine manufacturer and should be an official valid H.265 HEVC licensee and should be listed on HEVC H.264/ MJPEG website at the time of submitting bid.)
2	PTZ:- Pan: 360° endless/continuous, 250°/s (Auto), 0.1 to 200°/s (Manual). Tilt: -10° to +90° (Auto flip), 150°/s (Auto), 0.1 to 120°/s (Manual). 30x optical zoom and 12x digital zoom. 256 preset positions. Auto-Tracking. Pre-set tour.	Kindly change this with 1° to 240°/s and remove Auto-tracking	Pan: 360° endless/continuous, 250°/s (Auto), 0.1 to 240°/s (Manual). Tilt: -10° to +90° (Auto flip), 150°/s (Auto), 0.1 to 120°/s (Manual). 30x optical zoom and 12x digital zoom. 256 preset positions. Auto-Tracking . Pre-set tour.
3	Intelligent Video:- Motion Detection, Camera Tampering, Loitering, Line crossing, Intrusion, Human & Vehicle detection and Auto Tracking	Kindly remove Human & Vehicle detection and Auto Tracking	Motion Detection, Camera Tampering, Loitering, Line crossing, Intrusion, Human & Vehicle detection and Auto Tracking
	64 Channel NVR with 8 SATA Interface Loaded with 64TB Storage Capacity		
1	Video Output & Backup:- VGA and HDMI, 2 nos. of USB port, 1 no. e-SATA port, should support Network, USB & e-SATA data backup	Kindly remove VGA, 1 no. e-SATA & e-SATA data backup	VGA and HDMI, 2 nos. of USB port, 1 no. e-SATA port, should support Network, USB & e-SATA data backup
2	Alarm & Serial Interface:- Should support 16 Channels in & 4 out Alarm interfaces and 2 serial interfaces (RS232/RS485)	Kindly change this with 2 in 2 out	Should support 16 Channels in & 4, 2 in 2 out Alarm interfaces and 2 serial interfaces (RS232/RS485)

Executive Engineer
Capital Project Elect. Dn.

Gandhinagar

3

Recording Features:-

Should support ANR and Pre/Post recording

Kindly remove ANR

Should support ANR and Pre/Post recording



Executive Engineer
Capital Project Elect. Dn.
Gandhinagar

